



PROJECTOR LED SMD WITH ROTADED MOVEMENT DETECTOR 50W BLACK IP54 6500K PLUS

Code: 147-69069

TECHNICAL DATA

Series Number:	PLUS
Supply Voltage (V):	160-265V
Nominal Power (W):	50W
Amperage (A):	210mA
Operating Frequency (Hz):	50/60Hz
Led Type:	SMD2835
Color Temperature (K):	6500K
Luminous Flux (lm):	6000lm
Lumen/ Watt:	120Lm/Watt
Lumen/ Chip:	130Lm/chip
Watt/ Chip:	1W/Chip
Total Chips:	81pcs
Chip Size:	SMD2835
Chip Brand:	Sanan
Driver Brand:	EVR
Included Driver:	Ενσωματωμένο στην πλακέτα/ Embedded in plate
Power Factor (PF):	>0.90
Color Rendering Index CRI (Ra):	>70
Life Time (h):	30000h
Starting Time (sec):	0.5 sec
Switching Cycles (ON/ OFF):	25000
Dimmable:	Όχι/No
Energy Class:	E
Ingress Protection (IP):	IP54



Impact Resistant (IK):	IK06
Operating Temperature °C:	-20°C - +50°C
Beam Angle:	120°
Product Color:	Μαύρο/Black
Product Net Weight (kg):	0.600
Product Gross Weight (kg):	0.700
Packing (pcs):	1\20
Packaging:	Color Box
Height:	31.7mm
Width:	170mm
Length:	146.2mm
Guarantee Eurolamp:	3 Χρόνια/3 Years
Certifications:	Ναι/Yes
CE Mark:	Ναι/Yes
Installation Height:	2-3mtr
Insulation Rating:	Class I
Connection Type:	Καλώδιο/Wire
Grounding:	Ναι/Yes
Cable Length:	150mm
Cable Cross Section:	3x1.00mm ²
Detection Type:	Αισθητήρας Μικροκυμάτων/ Microwave Sensor
Product Info:	Γαλβανιζέ Βίδες / Galvanized Bolts
Product Info:	Turning the SENS dial anticlockwise will decrease the detection range (2m-10m). Turning the TIME dial anticlockwise will decrease the hold time (10 seconds-7minutes). Turning the LUX dial anticlockwise will restrict activation to lower light conditions(3
Product Info:	Detection Range: 120° Working Temperature: -20~+40°C Working Humidity: <24%

