

Date tehnice pentru produs: AT208061 --

# Dulap inseriabil 1 uşă IP55 H=2000 L=800 A=600 mm

Dulap oţel RAL7035, fără placă de montaj, uşă cu închidere în 4 puncte



## SCHRACK-Info

- **Material** : Frame: 1.5 mm sheet steel. Doors: Single door and double door: 1.5 mm sheet steel. Rear-, roof- and side-panels: 1.2 mm sheet steel
- **Mounting plate** : 3 mm galvanised sheet steel. Double folded, mounted in the enclosure, fully adjustable in depth in 25 mm increments
- **Bottom plates** : 1.5 mm galvanised sheet steel, consists of
  - three-part bottom plate at depths 400 and 500 mm and
  - four-part bottom plate at depth 600 mm
  - five-part bottom plate at depth 800 mm
- **Frame** : Folded and seam welded reversed open profile with 25 mm hole pattern according to DIN 43660. Including integrated external hole pattern
- **Door** : On single door enclosures, the door is mounted on four double-sided hinges for right-hand opening (= hinged right). Doors for left-hand opening (= hinged left) have to be ordered separately. On double door enclosures, hinges are not reversible. All door panels include the door mounting frame with 25 mm hole pattern. The left Z-wing is locked separately with an inner three-point lock
- **Lock** : Four-point rod lock with push-pull handle with spring adjustment and half cylinder lock 5333 (identical key), does not slide inward. The standard lock can be exchanged for profile half cylinder (DIN cylinder) and other inserts from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Rear panel** : Mounted with M6 torx screws. Replacement against additional door from the back side is possible. For 1600 mm wide enclosures the rear panel is divided

- **Side panels** : ATSW... supplied in pairs as accessory
- **Roof panel** : Removable
- **Earthing** : All panels are earthed through their fittings and are equipped with a separate earthing stud
- **Degree of protection** : Single door IP55 and double door IP54
- **Impact resistance** : IK10
- **Finish** : Textured powder coating
- **Color** : RAL7035 (Light grey)
- **Delivery includes** : Frame with fitted door, rear panel, roof panel, bottom plates, mounting plate with fixing material for the nearest position of the rear panel and earthing studs. Delivered on a pallet with equal width as the enclosure to enable bayging while still on the pallet. All packing material is recyclable. In 400 mm wide enclosures a mounting plate, bottom plates and door frame are not included
- **Mounting requirement** : Standard delivery ready for combined installation. For stand-alone installation add side panels



## Fișe tehnice

|                                            |                   |
|--------------------------------------------|-------------------|
| Lățime netă (mm)                           | 800,00            |
| Înălțime (mm)                              | 2.000,00          |
| Adâncime netă (mm)                         | 600,00            |
| Masă netă (kg.)                            | 98,00             |
| Temperatura minimă a mediului ambiant (°C) | -20               |
| Temperatura maximă a mediului ambiant (°C) | 70                |
| Material                                   | tablă de oțel     |
| Categorie produs                           | Modular enclosure |
| Total Load Capacity (kg.)                  | 1000              |
| Grosimea peretelui corpului (mm)           | 1,50              |
| Grad de protecție                          | IP55              |
| Contrapanouri                              | fără contrapanou  |
| Mounting Plate Load Capacity (kg.)         | 500               |
| Înălțimea contrapanoului (mm)              |                   |
| Lățimea contrapanoului (mm)                |                   |
| Adâncimea contrapanoului (mm)              |                   |
| Număr de uși                               | 1                 |
| Load capacity per door (kg.)               | 50                |
| Grosimea peretelui ușii (mm)               | 1,50              |
| Număr de plăci de bază                     | 4                 |
| Lățime placă de bază (mm)                  | 555               |
| Culoare                                    | Gri deschis       |
| disipare (W)                               | -976,00           |
| Clasă de protecție                         | I                 |

## Tabel articole

| Descriere                                                                                                                                                     | Cod comandă |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| Dulap inserabil 1 ușă IP55 H=2000 L=800 A=600 mm                                                                                                              | AT208061    |
| Dulap oțel RAL7035, fără placă de montaj, ușă cu închidere în 4 puncte                                                                                        |             |
| <b>Accesorii opționale</b>                                                                                                                                    |             |
| 2 panouri laterale H=2000 A=600 mm, tablă 1.2 mm RAL7035                                                                                                      | ATSW2006    |
| Plintă, Set 4 colțare 100mm, RAL7012                                                                                                                          | ATSOC104    |
| Plintă, Set 4 colțare 200mm, RAL7012                                                                                                                          | ATSOC204    |
| Plintă, Set laterale 600x100mm, RAL7012                                                                                                                       | ATSOT061    |
| Plintă, Set față și spate 800x100mm RAL7012, 2 buc. în furnitură                                                                                              | ATSOB081    |
| Kit inseriere dulapuri AT cu 4 piese de legătură cu 4x piese legătură, 2 urechi de ridicat, garnitură de 5,6m, 8xM6 suruburi de fixare și accesorii de montaj | ATCCI060    |
| Urechi de ridicare M12 pt. dulapuri AC și KC<br>1 Set=4 piese                                                                                                 | ACLE9301    |
| Suport documentație, autoadeziv, A4                                                                                                                           | ASDRA400    |
| DIN-rail low, unperforated, sendzimir zinced<br>Price per piece                                                                                               | BK14004--B  |
| Șină omega din oțel zincat, 2000x35x7,5mm, perforată<br>Pretul este pe bucata de 2 m.                                                                         | BK14005--A  |
| DIN-rail high, unperforated, sendzimir zinced<br>DIN-rail high, unperforated, sendzimir zinced                                                                | IL14035--A  |
| DIN-rail high, Long Hole 18x6.3mm, sendzimir zinced<br>Price per piece                                                                                        | IL14037     |