


NH fuse-base 160 A, panel mounting (03 758)



Description

Article

Part No.: 03 758

QUADRON® Panel

NH fuse-base 160 A, panel mounting

both sides screw

size 00 / 1P, with touch protection

System

Mounting plate

Product group 10

Subgroup 03

pack size 12

EAN 4021267037581

Advantages of the product

For safe connection of the leads, the shock protection is split into 2.

Catalog page 2015 : 6/13

eCl@ss 6.1 27142106
eCl@ss 7.1 27142106
ETIM 4.0 EC000067
ETIM 5.0 EC000067

Approvals

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014
IEC 60269-2:2013

Approvals

Germanischer Lloyd



Type number: NH-00

Product data

Electrical data

Rated current (IEC): 160 A
Rated voltage (IEC) AC: 690 V
Rated voltage (IEC) DC: 440 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 2.7 W.
(The power dissipation for operation with rated current would be 4.2 W.)

rated isolation voltage U_i (AC): 800 V
Rated surge voltage U_{imp} : 6 kV
max. permitted voltage (IEC) AC: 1000 V
max. permitted voltage (IEC) DC: 1000 V

breaking capacity with fuses: 50 kA

for fuse links IEC 60269-2 / DIN VDE 0636-201 size 00 up to 12W power dissipation

Mechanical data

W x H x D: 36 x 147 x 88

Weight: 15.2 kg/100

Poles: 1-pole

screw connection M8, 8 - 10Nm torque

Terminal points

NHUT_SCHRAUBE_M8


Material properties

Main body: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free

Contacts: spring-loaded copper contacts, silver plated
Connecting screw M8, galvanized, chromized
screws:

Shock protection cover: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free

Accessories



03 161
knife link 160 A
size 00



03 502
NH fuse extractor handle
open
size 000 - 3



03 519
neutral conductor 160 A
screw, both sides



03 620
neutral conductor 160 A
cleat, both sides



79 448
grip lug cover
for NH base and 33 705
NH 00