

Date tehnice pentru produs: H6USG30K0G

Patchcablu Cat.6 cu LED neecranat RJ45 gri 30m



SCHRACK-Info

Patchcords for generic, structured network cabling systems. Support all applications requiring Class D to Class E (e.g. 1000Base-T, 100Base-TX, ATM) as well as VoIP, PoE. On the RJ45 connector of the LED patchcord, there are two contacts for the Patchfinder tool. By connecting the Patchfinder to the contacts, the boots at both ends of the LED patchcord start to light. Thus the patching is easily identified. During Light-functionality, Data-transmission remains stable and is not affected. Pin assignment 1:1.

Fișe tehnice

Categorie	Cat.6
Construcție cablu	4x2xAWG24/7
Ecranaj	U/UTP
Conexiune	1:1
Bit rate	up to Gigabit Ethernet
Număr de perechi	4+1
Ecranaj	neecranat
Manta	LSOH
Funcționalitate LED	cu LED
Masă netă (kg.)	0,96
Culoare	gri

Fișe tehnice - Continuare

Temperatura minimă a mediului ambiant (°C)	-10
Temperatura maximă a mediului ambiant (°C)	50
RoHS	conform
Lungime patchcord (m.)	30,0
Conector standard	EN 60603-7
Tip conector	RJ45 unshielded
Pin assignment	EIA/TIA 568B 1:1

Tabel articole

Descriere	NVP (%)	Greutate cupru (kg/km)	Cod comandă
Patchcablu Cat.6 cu LED neecranat RJ45 gri 30m			H6USG30K0G
Accesorii opționale			
LED Detector Pro pentru patchcabluri cu LED, CPZLWLA2 cu baterii reîncărcabile și cablu de reîncărcare USB			HLEDTOOL1
Sculă identificare pentru Patchcablu cu LED H6G(U)SxxxK0x			HLEDTOOL
Modul RJ45 neecranat, Cat.6 De-embedded, TOOLLESS LINE			HSEMRJ6UWS
Patchpanel Cat.6 neecranat 24xRJ45U RAL7035			HSERU246GV
Cablu U/UTP Cat.6, 4x2xAWG24/1, 300MHz, LS0H, B2ca albastru albastru, Tambur 500m	68	19	HSKU423BP5
Cablu U/UTP Cat.6, 4x2xAWG24/1, LS0H, Eca, albastru, cutie Box 305m	69	18	HSEKU423H4
Cablu U/UTP Cat.6, 4x2xAWG24/1, PVC, Eca, albastru, cutie Box 305m	69	18	HSEKU423P4