

Date tehnice pentru produs: KC188041--

Dulap monobloc cu o ușă Î=1800 L=800 A=400

tablă oțel, RAL7035, fără placă de montaj, închidere în patru puncte, mâner tragere-apăsare



SCHRACK-Info

- **Material** : Corpus: 1.5 mm galvanised sheet steel. Doors: Single door and double door: 2 mm sheet steel
- **Mounting plate** : 3 mm galvanised sheet steel. Double folded, mounted in the enclosure, fully adjustable in depth in 25 mm increments with depth adjustment brackets ACMPD002. As insertion aid of the mounting plate we recommend the use of slide-in rails ACCLT300 (for depth 300 mm), ACCLT400 (for depth 400 mm) and ACCLT500 (for depth 500 mm). The slide-in rails are inserted in the floor, after sliding and fixing of the mounting plate they can be removed and reused in the next enclosure
- **Bottom plates** : 1 mm galvanised sheet steel, divided in two parts
- **Frame** : Folded and seam welded reversed open profile with 25 mm hole pattern according to DIN 43660. Including inside circumferential hole pattern
- **Door** : On single door enclosures, the door is mounted on four double-sided hinges allowing left- or right-hand opening. On double door enclosures, hinges are not reversible. Doors for left-hand opening have to be ordered separately. All door panels include the door mounting frame with 25 mm hole pattern. The left Z-wing is locked separately with an inner three-point lock
- **Lock** : Four-point rod lock with push-pull handle with spring adjustment and 5 mm DIN double-bit key lock (DDB), does not slide inward. The standard lock can be exchanged for profile half cylinder (DIN cylinder) and other inserts from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Rear panel** : Mounted with M6 torx screws. Replacement against additional door from the back side is possible. For 1600 mm wide enclosures the rear panel is divided
- **Roof panel** : Removable
- **Earthing** : All panels are earthed through their fittings and are equipped with a separate earthing stud
- **Degree of protection** : Single door and double door IP55
- **Impact resistance** : IK10

- **Finish** : Textured powder coating
- **Color** : RAL7035 (Light grey)
- **Delivery includes** : Enclosure with door, rear panel, roof panel, bottom plates, mounting plate with fixing material for the nearest position of the rear panel and earthing studs. Delivered on a pallet with equal width as the enclosure.



Fișe tehnice

Lățime netă (mm)	800,00
Înălțime (mm)	1.800,00
Adâncime netă (mm)	400,00
Masă netă (kg.)	99,20
Temperatura minimă a mediului ambiant (°C)	-10
Temperatura maximă a mediului ambiant (°C)	60
Material	tablă de oțel
Categorie produs	Compact enclosure
Total Load Capacity (kg.)	700
Grosimea peretelui corpului (mm)	1,50
Grad de protecție	IP55
Contrapanouri	fără contrapanou
Mounting Plate Load Capacity (kg.)	700
Număr de uși	1
Load capacity per door (kg.)	100
Grosimea peretelui ușii (mm)	2
Număr de plăci de bază	2
Lățime placă de bază (mm)	630
Culoare	Gri deschis
disipare (W)	-724,00
Clasă de protecție	I

Tabel articole

Descriere	Cod comandă
Dulap monobloc cu o ușă Î=1800 L=800 A=400 tablă oțel, RAL7035, fără placă de montaj, închidere în patru puncte, mâner tragere-apăsare	KC188041
Accesorii opționale	
Contrapanou din oțel galvanizat Î=1800 L=800 mm	ACMP1808
Set elemente laterale (pereche) soclu din oțel, A=400 Î=100mm preassembled, sheet steel RAL9005 (Jet black)	ACSOT041
Set elemente față-spate soclu din oțel, L=800 Î=100 mm RAL9005, 1 Set=2 buc	ACSOB081
Set elemente laterale (pereche) soclu din oțel, A=400 Î=200mm preassembled, sheet steel RAL9005 (Jet black)	ACSOT042
Set elemente față-spate soclu din oțel, L=800 Î=100 mm RAL9005, 1 Set=2 buc	ACSOB081
Acoperiș predecupat pentru plăci de trecere L800 A400m Potrivite pentru dulapuri AC/KC, plăci de trecere:	ACRCE0804
Șine glisare plăci montaj în dulapuri A=400, set de 2 buc. of series AC and KC, PU=1 pair	ACCLT400
Urechi de ridicare M12 pt. dulapuri AC și KC 1 Set=4 piese	ACLE9301
Suport documentație, autoadeziv, A4	ASDRA400
Piuliță clipsabilă M6 (1 set=10 buc.)	ACCNM615
Șurub cu cap bombat M6x16 conform ISO 7380 1 Set=10 piese	ACCNK006
Piuliță clipsabilă M8 (1 set=10 buc.)	ACCNM815
Șurub cu cap bombat M8x16 conform ISO 7380 1 Set=10 piese	ACCNK008
Cheie metalică cu 2 pini de 5 mm PU=1 piese	DV903532