

# Product datasheet

Specifications



impulse relay TL - 2P - 2 NO - 16A -  
coil 110 VDC - 230...240 VAC  
50/60Hz

15520

(!) Discontinued on: 17 Nov 2014

(!) End-of-service on: 16 Oct 2019

(!) Discontinued

## Main

Product or component type	Impulse relay
Device short name	TL
Device application	Remote control
Poles	2P
Pole contact composition	2 NO
[In] rated current	16 A
Network type	AC
[Uc] control circuit voltage	230...240 V AC 50/60 Hz 110 V DC

## Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50/60 Hz
control type	Coil disconnection Remote control
Control signal type	Impulse
Switching frequency	100 switching operations/day 5 switching operations/minute
Impulse duration	50 ms...1 s
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Electrical durability	AC-21: 200000 cycles AC-22: 100000 cycles
Range compatibility	Multi9 ATEt Multi9 ATL

## Environment

Standards	EN 669-1 EN 669-2-2
Product certifications	GOST
Quality labels	CEBEC IMQ NF VDE
Noise level	60 dB
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	1.8 cm
Package 1 Length	7.5 cm
Package 1 Weight	0.111 kg

## Contractual warranty

Warranty	18 months
----------	-----------