

■ Tuburi de capat duble, izolate 2 X 0.25 - 2 X 16 mm²

- Pentru conductoare multifilare cu liti fine si extrafine

Caracteristici


- Izolate, fara halogenuri
- Temperatura de lucru: pana la 105° C

Material

- Cupru EN 13600
- Izolatie sintetica: polipropilena

Suprafata


- Stanata



Sectiune mm ²	Cod	Culoare	Dimensiune mm						buc/pac
			d1	d3	l1	l2	s1	s2	
0,25	8678		1,15	1,8/3,4	15,0	8	0,15	0,25	100
0,34	8688		1,15	1,8/3,4	15,0	8	0,15	0,25	100
0,5	8698		1,50	2,5/4,7	15,0	8	0,15	0,25	100
0,75	8708		1,80	2,8/5,0	15,0	8	0,15	0,25	100
	87010		1,80	2,8/5,0	17,0	10	0,15	0,25	100
1	8718		2,05	3,4/5,4	15,0	8	0,15	0,30	100
	87110		2,05	3,4/5,4	17,0	10	0,15	0,30	100
1,5	8728		2,30	3,6/6,6	16,0	8	0,15	0,30	100
	87212		2,30	3,6/6,6	20,0	12	0,15	0,30	100
2,5	87310		2,90	4,2/7,8	18,5	10	0,20	0,30	100
	87313		2,90	4,2/7,8	21,5	13	0,20	0,30	100
4	87412		3,80	4,9/8,8	23,0	12	0,20	0,30	100
6	87514		4,90	6,9/10,0	26,0	14	0,20	0,40	100
10	87614		6,50	7,2/13,0	26,0	14	0,20	0,40	100
16	87714		8,30	9,6/18,4	30,0	14	0,20	0,40	100

■ Tuburi de capat, tip banda 0.5 - 2.5 mm²

- Dimensiune tub si culori conf. normei DIN 46228
- Pentru conductoare multifilare cu liti fine si extrafine



Caracteristici



- Izolate, fara halogenuri
- Temperatura de lucru: pana la 105° C

Material

- Cupru EN 13600
- Izolatie sintetica: polipropilena

Suprafata

- Stanata



Sectiune mm ²	Cod	Culoare	Dimensiune mm		buc/rola
			l1	l2	
0.5	ST9698		14	8	500
0.75	ST9708		14	8	500
1	ST9718		14	8	500
1.5	ST9728		14	8	500
2.5	ST9738		14	8	500