

■ DATA SHEET:  
WALL MOUNTING DISTRIBUTION CABINET WV L 1050



■ TECHNICAL DATA

- With profile mounting troughs for LSA modules
- One-part sheet steel door
- Cable entry via brushes on roof and base of the cabinet
- All conducting enclosures interconnected by earth cables
- Three point locking with swing handle prepared for lock (profil half cylinder)
- Document holder on the inside of the door

■ CLIMA AREA

Application in dry or humidity rooms, indoor.

- Protection class with out IP 54 kit: IP40
- Protection class with IP 54 kit: IP54

■ INTERIOR FITTINGS

- Horizontal and vertical jumper guides
- Potential equalisation by VDE 100
- Inclusive potential equalisation busbar (copper)
- Self-supporting rack
  - Profile mounting troughs: 3
  - Capacity per trough: 350 pairs, (36 LSA modules)
  - Maximum capacity: 1050 pairs, (3 x 36 LSA modules)

■ MECHANICAL DATA

- Material: sheet steel 2 mm
- Dimensions: width: 800 mm, height: 1300 mm, depth: 220 mm
- Colour: light grey, RAL 7035

DESCRIPTION	ORDER NO.
Telephony wallmount distribution cabinet 3x350 pairs back mount	HSTMWVL105