

ROS331----



EN 60670-1 (2005)
EN 60670-24 (2013)
Low voltage direct. 2014/35/EU



Serie Comerciala	Seria ENERBOX
Descriere	TABLOU DISTRIBUTIE ECHIPAT CU SIGURANTE
Tip montaj	APLICAT

CARACTERISTICI TEHNICE

Material	TERMOPLASTIC
Norma de referinta	EN 60439-1
Tensiune nominala	230V/400V, 50Hz
Grad protectie tablou IP	IP54
Grad protectie prize IP	IP44/IP54
Grad protectie mecanica IK	IK08
Clasa de protectie	II (izolatie)
Temperatura optima de operare	-25°C pana la +35°C
Temperatura maxima de operare	+60°C
Intrare cablu	PG21
Material rezistent UV	DA
Conexiune	max 10mm ²

DIMENSIUNI

Nr. module	6 MODULE
Dimensiuni tablou	145 X 285 X 106 mm

ECHIPARE TABLOU

Priza schuko 2P+E, 16A/230V	3 buc.
Interrupator automat 1P 16A	1 buc.

ENERBOX-1												
RATED VOLTAGE (V) Un = 230												
RATED CURRENT (A) In = 16												
RATED FREQUENCY (Hz) fn = 50-60												
PROTECTION DEGREE P44												
REFERENCE STANDARD EN61439-3												
ADEQUATELY PROTECTED UPSTREAM												
CIRCUIT												
COMPONENTS DESCRIPTION		EARTH	POWER SUPPLY									
PROTECTION DEVICES	TYPE			WCB								
	Un (V)			230								
	In (A)			16								
	N-POLES			1P+N								
	CHARACTERISTICS			CURVE "C"								
	BREAKING CAPACITY (kA)			4,5								
PLUGS AND SOCKETS	TYPE			UNEL	UNEL	UNEL						
	Un (V)			200-250	200-250	200-250						
	In (A)			16	16	16						
	N-POLES			2P+E	2P+E	2P+E						
	CONFIGURATIONS											
	SCAME PART NUMBER			570.4061	570.2561	570.2561						
TYPE TERMINALS	N° SECTION (mmq)	10	2x10									
CONNECTION	L1, L2, L3, N, PE	PE	L, N	L, N, PE	L, N, PE	L, N, PE						
	SEZ (mmq)	2,5	2,5	2,5	2,5	2,5						

REZISTENȚA LA ACȚIUNEA AGENȚILOR CHIMICI ȘI ATMOSFERICI

Soluții saline	Acizi		Baze		Solvenți				Ulei Mineral	Raze UV
	Concentrat	Diluat	Concentrat	Diluat	Hexan	Benzen	Acetona	Alcool		
Rezistent	Rezistență limitată	Rezistent	Rezistență limitată	Rezistent	Nerezistent	Nerezistent	Nerezistent	Rezistență limitată	Rezistent	Rezistent