

Date tehnice pentru produs: IK026210--

Clemă derivație, 35mm², 1 p., gri



Schrack-Info

- Suitable for copper conductors
- Protected against unintentional contact (IP20)
- Stackable


Fișe tehnice

Standard produs	IEC60947-7-1
Tensiune nominală	1000VAC/VDC
Current carrying capacity (A)	202A (2x25mm ²); 125A (1x35mm ²)
Terminal element	Brass (CuZn39Pb2)
Carcasă	PA 6 (halogen-free)
Screws	Steel, Zn thick-film passivated
Reacția la foc	Selbstverlöschend
Dimensiuni (mm)	1 polig: 29mm x 49,3mm x 55,4mm

Technical Data

Anschlussquerschnitte: (je Pol)	Rundleiter	Eindrchtig oder mehrdrchtig	Feindrchtig mit Aderenhlse
	2x35mm ²	4 - 35mm ²	2,5 - 25mm ²
	Abisolierlnge	22mm	
	Kreuzschlitzschraube	M8 (+/- PZ2)	
	Anzugdrehmoment	3,5Nm	
	2x25mm ²	2,5 - 25mm ²	1,5 - 16mm ²
	Abisolierlnge	18mm	
Flammwidrigkeit:	Kreuzschlitzschraube	M6 (+/- PZ2)	
	Anzugdrehmoment	2,5Nm	
		Selbstverlschend	

Desen dimensional: Clem derivaie, 35mm², 1p., gri



Descriere	Cod comand
Clem derivaie, 35mm ² , 1p., gri	IK026210